

## The Minimum Test Collection Problem

Anna Gorbenko

Department of Intelligent Systems and Robotics  
Ural Federal University  
620083 Ekaterinburg, Russia  
gorbenko.ann@gmail.com

Vladimir Popov

Department of Intelligent Systems and Robotics  
Ural Federal University  
620083 Ekaterinburg, Russia  
Vladimir.Popov@usu.ru

### Abstract

In this paper we consider an approach to solve the minimum test collection problem. This approach is based on an explicit reduction from the problem to the satisfiability problem.

**Keywords:** minimum test collection problem, satisfiability, **NP**-complete

Investigation of different regularities plays an important role for the detection of various knowledge (see e.g. [1] – [8]). In particular, the minimum test collection problem can be used for rapid identification of unknown pathogens (see e.g. [9]). Let

$$D = \{D[1], \dots, D[n]\},$$
$$T = \{T[1], \dots, T[m] \mid T[i] \subseteq D\}.$$

THE MINIMUM TEST COLLECTION PROBLEM (MTC):

INSTANCE: *Given a set  $D$  and a positive integer  $d$ .*

QUESTION: *Is there a set*

$$S \subseteq T$$

*such that  $|S| \leq d$  and for any  $1 \leq i < j \leq n$ , there is  $T[k] \in S$  such that*

$$|\{D[i], D[j]\} \cap T[k]| = 1?$$

Note that MTC is **NP**-complete (see e.g. [10]). Encoding hard problems as instances of SAT and solving them with different efficient satisfiability algorithms has caused considerable interest (see e.g. [11] – [15]). In this paper, we consider an approach to solve the MTC problem. Our approach is based on an explicit reduction from the problem to the satisfiability problem. Let

$$\begin{aligned}\varphi[1] &= \bigwedge_{1 \leq i \leq d} \bigvee_{1 \leq j \leq m} x[i, j], \\ \varphi[2] &= \bigwedge_{1 \leq i \leq d} \bigwedge_{1 \leq j[1] < j[2] \leq m} (\neg x[i, j[1]] \vee \neg x[i, j[2]]), \\ \varphi[3] &= \bigwedge_{1 \leq i \leq d} \bigwedge_{1 \leq j \leq m} \bigwedge_{1 \leq k \leq n, D[k] \in T[j]} (\neg x[i, j] \vee y[i, k]), \\ \varphi[4] &= \bigwedge_{1 \leq i < j \leq n} \bigvee_{1 \leq k \leq d} z[i, j, k], \\ \varphi[5] &= \bigwedge_{1 \leq i < j \leq n} ((\neg z[i, j, k] \vee y[k, i] \vee y[k, j]) \wedge (\neg z[i, j, k] \vee \neg y[k, i] \vee \neg y[k, j])).\end{aligned}$$

Let  $\xi = \bigwedge_{i=1}^5 \varphi[i]$ . It is easy to check that there is a set  $S \subseteq T$  such that  $|S| \leq d$  and for any  $1 \leq i < j \leq n$ , there is  $T[k] \in S$  such that  $|\{D[i], D[j]\} \cap T[k]| = 1$  if and only if  $\xi$  is satisfiable. It is clear that  $\xi$  is a CNF. So,  $\xi$  gives us an explicit reduction from MTC to SAT. Now, using standard transformations (see e.g. [16]) we can obtain an explicit transformation  $\xi$  into  $\zeta$  such that  $\xi \Leftrightarrow \zeta$  and  $\zeta$  is a 3-CNF. Clearly,  $\zeta$  gives us an explicit reduction from MTC to 3SAT. In papers [17, 18] the authors considered some satisfiability algorithms. Our computational experiments have shown that these algorithms can be used to solve MTC.

**ACKNOWLEDGEMENTS.** The work was partially supported by Analytical Departmental Program “Developing the scientific potential of high school” 8.1616.2011.

## References

- [1] V. Popov, The approximate period problem for DNA alphabet, *Theoretical Computer Science*, 304 (2003) 443-447.
- [2] A. Gorbenko and V. Popov, Multiple Occurrences Shortest Common Superstring Problem, *Applied Mathematical Sciences*, 6 (2012) 6573-6576.
- [3] V. Popov, Approximate Periods of Strings for Absolute Distances, *Applied Mathematical Sciences*, 6 (2012) 6713-6717.
- [4] V. Popov, The Approximate Period Problem, *IAENG International Journal of Computer Science*, 36 (2009) 268-274.

- [5] V. Popov, Multiple genome rearrangement by swaps and by element duplications, *Theoretical Computer Science* 385 (2007) 115-126.
- [6] A. Gorbenko and V. Popov, The Binary Paint Shop Problem, *Applied Mathematical Sciences*, 6 (2012) 4733-4735.
- [7] V. Yu. Popov, Computational complexity of problems related to DNA sequencing by hybridization, *Doklady Mathematics*, 72 (2005) 642-644.
- [8] A. Gorbenko and V. Popov, Self-Learning Algorithm for Visual Recognition and Object Categorization for Autonomous Mobile Robots, *Lecture Notes in Electrical Engineering*, 107 (2012), 1289-1295.
- [9] G. Lancia and R. Rizzi, The approximability of the String Barcoding problem, *Algorithms for Molecular Biology*, 1 (2006), 12.
- [10] M.R. Garey and D.S. Johnson. Computers and Intractability; A Guide to the Theory of NP-Completeness. W. H. Freeman & Co., New York, NY, USA, 1979.
- [11] A. Gorbenko and V. Popov, The Far From Most String Problem, *Applied Mathematical Sciences*, 6 (2012) 6719-6724.
- [12] A. Gorbenko and V. Popov, The set of parameterized k-covers problem, *Theoretical Computer Science*, 423 (2012) 19-24.
- [13] A. Gorbenko and V. Popov, The Longest Common Parameterized Subsequence Problem, *Applied Mathematical Sciences*, 6 (2012) 2851-2855.
- [14] A. Gorbenko and V. Popov, On the Longest Common Subsequence Problem, *Applied Mathematical Sciences*, 6 (2012) 5781-5787.
- [15] A. Gorbenko and V. Popov, The Hamiltonian Alternating Path Problem, *IAENG International Journal of Applied Mathematics*, 42 (2012) 204-213.
- [16] A. Gorbenko and V. Popov, The c-Fragment Longest Arc-Preserving Common Subsequence Problem, *IAENG International Journal of Computer Science*, 39 (2012), 231-238.
- [17] A. Gorbenko and V. Popov, Computational Experiments for the Problem of Selection of a Minimal Set of Visual Landmarks, *Applied Mathematical Sciences*, 6 (2012), 5775-5780.
- [18] A. Gorbenko and V. Popov, Task-resource Scheduling Problem, *International Journal of Automation and Computing*, 9 (2012), 429-441.

**Received: December 3, 2012**